

PRODUCTS COMPANY LIMIT		ΛΔΤ	-==	ειΔι	SAF	= T	ПАТ	4 SHEET	
					ICT IDENTIFIC				
PRODUCT	<u> </u>			NODO			PRODUCT IDENTIFIC	ATION	
IDENTIFIER Silicone Rubber Se	ealant, SC	CS1003 12R-C	ortrg (0.73)	0 Lbs-0.33	1 Kg) Black		NUMBER (PIN)		
PRODUCT USE Sealant									
MANUFACTURER'S NAME GES Waterford Plant Supplier's NAME Alltemp Products Limited									
STREET ADDRESS 260 Hudso	on Rive	er Rd			STREET ADDRES	STREET ADDRESS 827 Brock Road S.			
CITY Waterford PROVINCE N		PROVINCE N	Y , USA		CITY Pickerin	CITY Pickering		ICE Ontario, Canada	
POSTAL CODE 12188	EMERGENCY TEL 1-800-424-				POSTAL CODE	L1W 3J2 EMERG		SENCY TELEPHONE NO.	
		SECT	TION 2) — НД	AZARDOUS IN	IGREDIE	ENTS		
HAZARDOUS INGR	EDIENTS	OLO!	HON 2 — HAZA		CAS NUMBER	LD50 OF INGREDIENT		LC50 OF INGREDIENT	
Mathyltriacotov	voilono.		1-5%		4253-34-3	(SPECIFY SPECIES AND ROUTE) N/A		(SPECIFY SPECIES) N/A	
Methyltriacetoxy Octamethylcycloteti				5%	556-67-2		N/A	N/A	
SILOXANES & SILICONES, DIMETHYL-POLYMERS W/ METHYLSILSESQUIOXANES				10%	68554-67-6		N/A	N/A	
Treated Filler			5 - 10 %		68611-44-9				
Dimethylpolysilo	oxane		60 - 90 %		70131-67-8				
			SECT	TION 3	— PHYSICAL	DATA			
PHYSICAL STATE ODOUR AND APPEARANCE Solid Acetic Acid odor				1111313/1			ODOUR THRESHOLD (ppm) Not available		
VAPOUR PRESSURE VAPOUR DENSITY (AIR=1) not applicable		EVAPORATION R		TION RATE	BOILING POINT (°C) N/A		FREEZING POINT (°C) N/A		
pH SPECIFIC GRAVITY 1.06		COEFF. WATER/OIL DIST. N/A		ATER/OIL DIST.					
	SECTION 4 — FIRE AND EXPLOSION DATA								
FLAMMABILITY									
YES NO IF YES, UNDER WHICH CONDIT	IONS?								
MEANS OF EXTINCTION									
FLASHPOINT (°C) AND METHOD			UPPER FLA (% BY VOL	AMMABLE LIN UME)	MIT			VER FLAMMABE LIMIT BY VOLUME)	
AUTOIGNITION TEMPERATURE (°C)			HAZARDOUS COMBUSTION PRODUCTS						
EXPLOSION SENSITIVITY TO IMPACT SENSITIVITY TO STATIC DISCHARGE									
DATA									
CHEMICAL STABILITY			SECT	ION 5 -	— REACTIVIT	Y DATA			
YES									
INCOMPATIBILITY WITH OTHER SUBSTANCES NO IF SO.									
WHICH ONES? REACTIVITY, AND UNDER WHAT CONDITIONS									
Not available HAZARDOUS DECOMPOSITION PRODUCTS Carbon dioxide (CO2) formaldehyde Carbon monoxide Acetic acid Silicon dioxide.									

PRODUCT

IDENTIFIER Silicone Rubber Sealant, SCS1003 12R-Crtrg (0.730 Lbs-0.331 Kg) Black

SECTION 6 — TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY

SKIN CONTACT EYE CONTACT INGESTION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT INGESTION: May be harmful if swallowed. SKIN: May cause mild skin irritation. INHALATION: None known.

EYES: May cause mild eye irritation.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT

This product or one of its ingredients present 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

EXPOSURE LIMITS	IRRITANCY OF PRODUCT	SENSITIZATION TO PRODUCT	CARCINOGENICITY
Not Available	Not Available	Not Available	None known
TERATOGENICITY	REPRODUCTIVE TOXICITY	MUTAGENICITY	SYNERGISTIC PRODUCTS
Not Available	Not Available	Not Available	Not Available

SECTION 7 — PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT					
GLOVES (SPECIFY)	RESPIRATOR (SPECIFY)	EYE (SPECIFY)			
Cloth gloves	If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations	Safety glasses			
FOOTWEAR (SPECIFY)	CLOTHING (SPECIFY)	OTHER (SPECIFY) Wear suitable protective clothing and			
N/A	N/A	eye/face protection.			

ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS.)

Eyewash stations Showers Exhaust ventilation

LEAK AND SPILL PROCEDURE

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Increase area ventilation.

WASTE DISPOSAL

Dispose of in accordance to federal provincial and local regulations

HANDLING PROCEDURES AND EQUIPMENT

N/A

STORAGE REQUIREMENTS

Use only in well-ventilated areas. Avoid contact with skin and eyes. Keep away from children. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Store away from heat, sources of ignition, and

SPECIAL SHIPPING INFORMATION

Chemical Name	Class	Subclass	Small Means of Containment	Consumer Commodities		
Shipping not regulated						

SECTION 8 — FIRST AID MEASURES

SPECIFIC MEASURES

INGESTION: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person. SKIN: To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. Get medical attention if irritation persists. INHALATION: If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists. Silicone Rubber Sealant, SCS1705 12R-Crtrg (0.730 Lbs-0.331 Kg) Almond

SECTION 9 — PREPARATION DATE OF MSDS

PREPARED BY (GROUP, DEPARTMENT, ETC.)
Health and Safety Department

PHONE NUMBER 1-800-263-4624 DATE 02/05/10

